

(2), said enclosure being provided with microwave energy transmission means (10) and presenting two opposite walls (15, 16) that are proof against microwave radiation and not airtight. The microwave radiation is used to limit quickly and cheaply phenomena of frosting or icing on the evaporator (2) so as to improve refrigeration performance.

12 Claims, 5 Drawing figures

Full	Title	Citation	Front	Review	Classification	Date	Reference	Sequences	Attachments
Draw Desc	Image								

KIMC

[Generate Collection](#)[Print](#)

Term	Documents
THERMAL.DWPI,TDBD,EPAB,JPAB,USPT,PGPB.	1008413
THERMALS.DWPI,TDBD,EPAB,JPAB,USPT,PGPB.	210
CONTACT.DWPI,TDBD,EPAB,JPAB,USPT,PGPB.	2682711
CONTACTS.DWPI,TDBD,EPAB,JPAB,USPT,PGPB.	643610
(5 AND (THERMAL ADJ CONTACT)).USPT,PGPB,JPAB,EPAB,DWPI,TDBD.	5
(L5 AND (THERMAL ADJ CONTACT)).USPT,PGPB,JPAB,EPAB,DWPI,TDBD.	5

Display Format:

-

[Change Format](#)[Previous Page](#)[Next Page](#)

WEST[Help](#)[Logout](#)[Interrupt](#)[Main Menu](#)[Search Form](#)[Posting Counts](#)[Show S Numbers](#)[Edit S Numbers](#)[Preferences](#)[Cases](#)**Search Results -**

Term	Documents
MAGNET.DWPI,TDBD,EPAB,JPAB,USPT,PGPB.	309197
MAGNETS.DWPI,TDBD,EPAB,JPAB,USPT,PGPB.	124017
(9 AND MAGNET).USPT,PGPB,JPAB,EPAB,DWPI,TDBD.	19
(L9 AND MAGNET).USPT,PGPB,JPAB,EPAB,DWPI,TDBD.	19

Database:

US Patents Full-Text Database
US Pre-Grant Publication Full-Text Database
JPO Abstracts Database
EPO Abstracts Database
Derwent World Patents Index
IBM Technical Disclosure Bulletins

Search:

L10

[Refine Search](#)[Recall Text](#)[Clear](#)**Search History****DATE:** **Monday, April 21, 2003** [Printable Copy](#) [Create Case](#)

Set Name Query

side by side

Hit Count Set Name

result set

DB=USPT,PGPB,JPAB,EPAB,DWPI,TDBD; PLUR=YES; OP=ADJ

<u>L10</u>	L9 and magnet	19	<u>L10</u>
<u>L9</u>	L8 and control\$3	59	<u>L9</u>
<u>L8</u>	L7 and (cooling adj system)	59	<u>L8</u>
<u>L7</u>	(temperature adj sensor) and (humidity adj sensor) and (pressure adj sensor)	532	<u>L7</u>
<u>L6</u>	L5 and (thermal adj contact)	5	<u>L6</u>
<u>L5</u>	L3 and magnet\$3	78	<u>L5</u>
<u>L4</u>	L3 and (magnetic adj resonance)	0	<u>L4</u>
<u>L3</u>	L2 and (temperature adj sensor)	603	<u>L3</u>
<u>L2</u>	L1 and (humidity adj sensor)	883	<u>L2</u>
<u>L1</u>	((temperature adj control) or refrigeration) and humidity	9042	<u>L1</u>

END OF SEARCH HISTORY

WEST[Help](#)[Logout](#)[Interrupt](#)[Main Menu](#)[Search Form](#)[Posting Counts](#)[Show S Numbers](#)[Edit S Numbers](#)[Preferences](#)[Cases](#)**Search Results -**

Term	Documents
MAGNET DWPI,TDBD,EPAB,JPAB,USPT,PGPB.	309197
MAGNETS DWPI,TDBD,EPAB,JPAB,USPT,PGPB.	124017
(9 AND MAGNET).USPT,PGPB,JPAB,EPAB,DWPI,TDBD.	19
(L9 AND MAGNET).USPT,PGPB,JPAB,EPAB,DWPI,TDBD.	19

Database:

US Patents Full-Text Database
US Pre-Grant Publication Full-Text Database
JPO Abstracts Database
EPO Abstracts Database
Derwent World Patents Index
IBM Technical Disclosure Bulletins

Search:

L10

[Refine Search](#)[Recall Text](#)[Clear](#)**Search History****DATE:** **Monday, April 21, 2003** [Printable Copy](#) [Create Case](#)

Set Name Query

side by side

Hit Count Set Name

result set

DB=USPT,PGPB,JPAB,EPAB,DWPI,TDBD; PLUR=YES; OP=ADJ

<u>L10</u>	L9 and magnet	19	<u>L10</u>
<u>L9</u>	L8 and control\$3	59	<u>L9</u>
<u>L8</u>	L7 and (cooling adj system)	59	<u>L8</u>
<u>L7</u>	(temperature adj sensor) and (humidity adj sensor) and (pressure adj sensor)	532	<u>L7</u>
<u>L6</u>	L5 and (thermal adj contact)	5	<u>L6</u>
<u>L5</u>	L3 and magnet\$3	78	<u>L5</u>
<u>L4</u>	L3 and (magnetic adj resonance)	0	<u>L4</u>
<u>L3</u>	L2 and (temperature adj sensor)	603	<u>L3</u>
<u>L2</u>	L1 and (humidity adj sensor)	883	<u>L2</u>
<u>L1</u>	((temperature adj control) or refrigeration) and humidity	9042	<u>L1</u>

END OF SEARCH HISTORY

WEST[Help](#)[Logout](#)[Interrupt](#)[Main Menu](#)[Search Form](#)[Posting Counts](#)[Show S Numbers](#)[Edit S Numbers](#)[Preferences](#)[Cases](#)**Search Results -**

Term	Documents
THERMAL.DWPI,TDBD,EPAB,JPAB,USPT,PGPB.	1008413
THERMALS.DWPI,TDBD,EPAB,JPAB,USPT,PGPB.	210
CONTACT.DWPI,TDBD,EPAB,JPAB,USPT,PGPB.	2682711
CONTACTS.DWPI,TDBD,EPAB,JPAB,USPT,PGPB.	643610
(5 AND (THERMAL ADJ CONTACT)).USPT,PGPB,JPAB,EPAB,DWPI,TDBD.	5
(L5 AND (THERMAL ADJ CONTACT)).USPT,PGPB,JPAB,EPAB,DWPI,TDBD.	5

Database:

US Patents Full-Text Database
US Pre-Grant Publication Full-Text Database
JPO Abstracts Database
EPO Abstracts Database
Derwent World Patents Index
IBM Technical Disclosure Bulletins

Search:

L6

[Refine Search](#)[Recall Text](#)[Clear](#)**Search History****DATE:** Monday, April 21, 2003 [Printable Copy](#) [Create Case](#)

Set Name Query
side by side**Hit Count Set Name**
result set*DB=USPT,PGPB,JPAB,EPAB,DWPI,TDBD; PLUR=YES; OP=ADJ*

<u>L6</u>	L5 and (thermal adj contact)	5	<u>L6</u>
<u>L5</u>	L3 and magnet\$3	78	<u>L5</u>
<u>L4</u>	L3 and (magnetic adj resonance)	0	<u>L4</u>
<u>L3</u>	L2 and (temperature adj sensor)	603	<u>L3</u>
<u>L2</u>	L1 and (humidity adj sensor)	883	<u>L2</u>
<u>L1</u>	((temperature adj control) or refrigeration) and humidity	9042	<u>L1</u>

END OF SEARCH HISTORY